Custom Series 250-T, 400-T, and 550-T Thermal Door Quote/Order Request Form

Fax Completed Checklist to U.S. Aluminum Technical Sales at (866) 262-3299. Then call to discuss: (800) 262-5151 (U.S.), (877) 421-6144 (Canada), or (323) 588-1281 (International). Ask for Extension 5305. This form is also available online at **usalum.com**.

COMPANY NAME _____ **PHONE** _____

CONTACT _____ **ACCOUNT NO.** _____ **FAX** _____

JOB NAME _____ **EMAIL** _____

❑ **QUOTE** ❑ **ORDER P.O. #** _____ **DATE** _____

SERIES	THICKNESS	STANDARD PROFILE DIMENSIONS STILE	TOP RAIL	BOTTOM RAIL
250T NARROW STILE	1-3/4"	3"	2-7/8"	4-5/16"
400T MEDIUM STILE	1-3/4"	4-1/4"	4-5/16"	7-1/4"
550T WIDE STILE	1-3/4"	5-1/2"	6"	7"

DOOR SWING CHART



Use the Door Swing Chart to determine how the door(s) should be handed.

DOOR OPENING SIZE

- ❑ 36" x 84"
- ❑ Custom Single _____
  Door Tag # _____
- ❑ 72" x 84"
- ❑ Custom Pair _____
  Door Tag # _____
  Maximum Leaf Size 48" x 96"

GLASS STOP

1" (25 mm) Square Glass Stops

TOP RAIL

- ❑ Standard
- ❑ 2-7/8" HT201
- ❑ 4-5/16" HT101
- ❑ 6" WT200
- ❑ Custom _____

BOTTOM RAIL

- ❑ Standard
- ❑ 4-5/16" HT101
- ❑ 7-1/4" JT650
- ❑ 7" WT100
- ❑ 10" A.D.A Compliant
- ❑ Custom _____

DOOR HINGING

- ❑ Top/Bottom and Intermediate Offset Pivots
- ❑ Additional Pivot
  Add _____ per Door
- ❑ 1-1/2 Pair Butt Hinges
- ❑ Additional Butt Hinge
  Add _____ per Door
- ❑ Continuous Geared Hinge
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only
  NOTE: Prep Only Requires Manufacturer's Name , Model, and Template
  Manufacturer: _____
  Model: _____
  _____

DOOR STILE / APPLICATION

Thermal Entrance

- ❑ 250-T Narrow — Light to Moderate Traffic
- ❑ 400-T Medium — Moderate to Heavy Traffic
- ❑ 550-T Wide — Heavy Traffic

LOCKING OPTIONS

- ❑ MS Hookbolt With Two Cylinders - **STD**
- ❑ Long Throw Deadlock With Cylinders
- ❑ 3-Point Locking @ Pair With Cylinders
- ❑ Latch/Deadlock (DH189) With Cylinders (Available for Series 250-T and 400-T only)
- ❑ Thumbturn in Lieu of Cylinder
- ❑ Latchlock (DH002)
- ❑ Cylinder (Ext.) ❑ Thumbturn (Int.)
- ❑ Lock Indicator
- ❑ Cylinder Guard
- ❑ Flushbolts
- ❑ Paddle Handle
- • DH569 Lever Handle
  ❑ Interior ❑ Back to Back
- • CRL DH52150 Lever Handle
  ❑ Interior ❑ Back to Back
- ❑ Electric Strike
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only
  NOTE: Prep Only Requires Manufacturer's Name , Model, and Template
  Manufacturer: _____
  Model: _____
  _____

DOOR FINISH

- ❑ 11 - Clear Anodized Class II - Standard
- ❑ 22 - Dark Bronze Anodized Class I - Standard
- ❑ 12 - Clear Anodized Class I
- ❑ 33 - Black Anodized Class I
- ❑ 52 - Bone White 70% KYNAR® (2-Coat)
- ❑ 71 - Standard 70% KYNAR® (2-Coat)
  Standard Color per Chart- Specify
  _____
- ❑ 71 - Custom 70% KYNAR® (2-Coat) - Specify
  _____
- ❑ 71 - Custom 70%KYNAR®(3-Coat) - Specify
  _____

DOOR SWING / QTY

- ❑ LHR Hinge Left Swing Out _____ ea.
- ❑ RHR Hinge Right Swing Out _____ ea.
- ❑ LH Hinge Left Swing In _____ ea.
- ❑ RH Hinge Right Swing In _____ ea.
- ❑ PAIR Swing In _____ ea.
- ❑ PAIR Swing Out _____ ea.

PANIC DEVICES

- ❑ Jackson 1285 Concealed Vertical Rod Panic (Available for Series 400-T and 550-T only)
- ❑ Jackson 1295 Rim Panic Device
- ❑ Jackson 2086 Concealed Vertical Rod Panic (Available for Series 400-T and 550-T only)
- ❑ Jackson 2095 Rim Panic Device
- ❑ Jackson 1085 Concealed Vertical Rod Panic (Available for Series 400-T and 550-T only)
- ❑ Jackson 1095 Rim Panic Device
- ❑ Adams-Rite 8400 Mortise Panic Device
- ❑ Adams-Rite 8600 Concealed Vertical Rod Panic (Available for Series 400-T and 550-T only)
- ❑ Adams-Rite 8800 Rim Panic Device
  ❑ Exit Only
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only
  NOTE: Prep Only Requires Manufacturer's Name , Model, and Template
  Manufacturer: _____
  Model: _____
  _____

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____

AVD8847 01.22.18

Custom Series 250-T, 400-T, and 550-T Thermal Door Quote/Order Request Form

Fax Completed Checklist to U.S. Aluminum Technical Sales at (866) 262-3299. Then call to discuss: (800) 262-5151 (U.S.), (877) 421-6144 (Canada), or (323) 588-1281 (International). Ask for Extension 5305. This form is also available online at **usalum.com**.

PUSH/PULL HARDWARE

- ❑ Standard Push/Pull
- ❑ Offset Pulls
- ❑ None No Prep _____
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only

NOTE: Prep Only Requires Manufacturer's Name , Model, and Template

Manufacturer: _____

Model: _____

_____

DOOR CLOSER

- ❑ O.H. Concealed (Offset-Prep Only)
  - 250-T and 400-T only with HT101 Top Rail
- ❑ Standard Jackson Closer (Supply)
  - 250-T and 400-T only with HT101 Top Rail
- ❑ 90° ❑ 105° Hold Open ❑ Yes ❑ No
- ❑ CRL Surface Mount Closer (Supply)
- ❑ Drop Plate
- ❑ Door Stop/Holder Degree _____
- ❑ No Closer Required
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only

NOTE: Prep Only Requires Manufacturer's Name , Model, and Template

Manufacturer: _____

Model: _____

_____

MUNTINS FOR SERIES 250-T AND 400-T ONLY

- ❑ 2-1/8"
- ❑ 3-9/16"
- ❑ 6-1/2"
- ❑ 9-1/4"

HARDWARE FINISH	DOOR FINISH
• Clear	11, 12, 44, 52, 71
• Bronze	22, 33

❑ Specify

_____

DOOR SWEEP

- ❑ Yes ❑ No
- ❑ Exposed Fasteners
- ❑ Concealed Fasteners

CLEARANCES/THESHOLD

Clearance from Bottom of Door to Finish Floor

- ❑ Custom

  Specify _____
- ❑ 4-3/4" (120.7 mm)
- ❑ 5" (127 mm)
- ❑ 7" (178 mm)
- ❑ None (No Allowance)

FRAME SYSTEM

Series IT451 2" x 4-1/2" ❑ Tubular ❑ Open Back

Subframe ❑ 1" x 4-1/2" (Thermal) Tubular Only

FRAME TYPE

- ❑ Up and Over (No Transom)
- ❑ 126" (3.2 m) High With Transom
- ❑ Frame Only
- ❑ Door Only (No Frame)
- ❑ Custom

_____

ADDITIONAL NOTES OR SKETCHES

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____

APPROVED BY _____ **DATE** _____

AVD8847 01.22.18